

medRAD[®] Salient
Contrast Injection System




medRAD[®] Salient

Your Partner for Mammography

MEDRAD® Salient Contrast Injection System

Easy syringe loading




Icon-driven user touch
screen



Reproducible injection
protocols



Complete range of
consumables



Real-time injection
pressure and flow metrics



Review 100
previous injection
profiles



Infrared remote control
for easy and safe
operation

MEDRAD® Salient

Main features of the Salient injector that make it ideal for Digital Mammography suites are:

Salient™ Dual Features

- » Dual action loading, for maximum ease of use
- » User friendly touch screen interface
- » On or off line contrast loading available
- » Infrared remote
- » 300psi pressure limit
- » Up to 10ml/s flow rate
- » Cordless battery powered

Easy To Use

- » Streamlined, icon driven touch screen
- » Easy to program routine or multiphase protocols
- » Quick Use Guide supplied for easy set up
- » Designed to fit in with your workflow

Patient And Operator Safety

- » No cords or cables to trip over
- » Easy to move: saves back and neck strain

Flexible, Reliable Performance

- » Battery powered, mains connection allows simultaneous operation and battery charging
- » Self test on start up
- » Backed by Bayer's commitment to providing excellent customer service and support

Mobility And Convenience

- » Large, lockable wheels for ease of manoeuvrability
- » Compact design
- » Light weight

Economical

- » Designed to maximise value: power where needed
- » Complete range of value consumables
- » Easy to clean, service and maintain

MEDRAD® Salient Contrast Injection System

MEDRAD Salient™ Contrast Injector Specifications Overview

Functional	
Maximum pressure	300 psi
Flow rate	0.1 to 10 ml/s
Maximum volume	190 ml
Multi-phase protocols	Up to six phases (Storage for 20 different named protocols)
Manual/Auto fill rate	Up to 10 ml/s
Controls	
Base	Line power On/off switch
Head	5.7" LCD touch screen Arm button On/off soft switch
Hand switch (optional)	Inject now/stop
Foot switch (optional)	Inject now/stop
Infrared Remote control	Inject now/stop

Mechanical	
Weight	25.5 kg
Height	1315 mm
Floor area	500 mm x 500 mm
No. of wheels	4 castors, all individually locking
Electrical	
Line voltage	100 – 230 VAC
Line frequency	50/60 Hz
Battery operation	Dual batteries, sealed lead acid
Mains power operation	Simultaneous operation and battery charging
Contrast heat maintainer (one included)	37°C +/- 4°C, 5W

Ordering Details

PART NAME	PART NO.
Salient Dual Injector	DC009D
Salient Dual Injector with Wireless Control Unit	DC009DW
Salient Single Injector	DC009S
Salient Single Injector with Wireless Control Unit	DC009SW
Connector Tubing Single (Box of 50)	ZY5151
Connector Tubing Dual (Box of 50)	ZY5152
Syringe with quick fill tube (Box of 50)	ZY6320
Heat maintainer (one included)	DC022



Bayer reserves the right to modify the specifications and features described herein or to discontinue any product or service identified in this publication at any time without prior notice or obligation. Please contact your authorized Bayer representative for the most current information.

Bayer, the Bayer Cross, MEDRAD, MEDRAD Salient are trademarks owned by and/or registered to Bayer in the U.S. and/or other countries. Other trademarks and company names mentioned herein are properties of their respective owners and are used herein solely for informational purposes. No relationship or endorsement should be inferred or implied.

© 2020 Bayer. This material may not be reproduced, displayed, modified or distributed without the express prior written consent of Bayer.



More information on
radiology.bayer.com



Manufacturer
Bayer Medical Care Inc. 1 Bayer
Drive Indianola, PA 15051-0780
U.S.A.
Phone: +1-412-767-2400
+1-800-633-7231
Fax: +1-412-676-4120

Hong Kong Distributor
Prism Technologies Limited
Unit 604, 6/F, Yee Kuk Industrial Centre,
555 Yee Kuk Street, Cheung Sha Wan,
Kowloon, Hong Kong
Phone: +852 2786 3233
Fax: +852 2786 3812